According to regulation (EC) No. 1907/2006 (REACH)

KREMER

70520 Shellsol® A

Page 1

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

1. Identification of the Substance/Mixture and of the Company/Undertaking

1. 1. Product Identifier

Product Name: Shellsol® A

Article No.: 70520

UFI:

1. 2. Relevant identified Uses of the Substance or Mixture and Uses advised against

Identified uses:

Industrial application

Uses advised against:

1. 3. Details of the Supplier of the Safety Data Sheet (Producer/Importer)

Company: Kremer Pigmente GmbH & Co. KG

Address: Hauptstr. 41-47, 88317 Aichstetten, Germany

Tel./Fax.: Tel +49 7565 914480, Fax +49 7565 1606

Internet: www.kremer-pigmente.com

EMail: info@kremer-pigmente.com

Importer: --

1. 4. Emergency No.

Emergency No.: +49 7565 914480 (Mon-Fri 8:00 - 17:00)

1. 4. 2 Poison Center:

2. Hazards Identification

2. 1. Classification of the Substance or Mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Flammable liquids, hazard category 3 Aspiration hazard, hazard category 1

Specific Target Organ Toxicity (single exposure), hazard category

3

Chronic aquatic toxicity, hazard category 2

H226 Flammable liquid and vapour.

Cat.: 3

H304 May be fatal if swallowed and enters airways.

Cat.: 1

H335 May cause respiratory irritation.

Cat.: 3

H336 May cause drowsiness or dizziness.

Cat.: 3

H411 Toxic to aquatic life with long lasting effects.

Cat.: 2

Possible Environmental Effects:

The product is combutible and can be ignited by potential sources of ignition. Spillage and extinguishing water can cause pollution of

the environment.

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 2

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

2. 2.

Classification according to Regulation (EC) No. 1272/2008 (CLP/GHS)

Hazard designation:



GHS02



GHS07



GHS08-2



GHS09

Signal word:

Danger

Hazard designation:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Safety designation:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No

smoking.

P301+P310 If swallowed: Immediately call a poison center or physician.

P331 Do not induce vomiting.

P370+P378 In case of fire: use water spray, foam, carbon dioxide or dry

extinguishing powder for extinction.

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P403+P235 Store in a well ventilated place. Keep cool.

Hazardous components for labelling:

2. 3. Other Hazards

3. Composition/Information on Ingredients

3. 1. Substance

3. 2. Mixture

Chemical Characterization: Aromatic hydrocarbons, C9.

Information on Components / Hazardous

Ingredients:

Hydrocarbons, C9, Aromatics (H226-304-335- 100 %

next page:

According to regulation (EC) No. 1907/2006 (REACH)

KREMER

70520 Shellsol® A

Page 3

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

336-411); REACH Reg. No. 01-2119455851-35-

XXXX EINECS-Nr: 918-668-5

EC-Nr:

CAS-Nr: 64742-95-6

Additional information:

4. First Aid Measures

4. 1. Description of the First Aid Measures

General information:

First aiders have to protect themselves.

Take person away from hazardous area.

Remove contaminated clothes immediately.

After inhalation:

Supply fresh air. If required give artificial respiration. Keep patient

warm.

In case of unconsciousness place patient stable in side position for

transportation.

In case of irritation of the respiratory system seek medical help.

After skin contact:

Wash off with plenty of water and soap.

After eye contact:

Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact

lenses. Continue to rinse for at least 10 minutes.

After ingestion:

Rinse mouth with plenty of water.

Do not induce vomiting. Consult physician immediately.

4. 2. Most important Symptoms and Effects, both Acute and Delayed

Symptoms:

Headache, dizziness, breathing difficulties, narcotic effects.

Effects:

4. 3. Indication of any Immediate Medical Attention and special Treatment needed

Treatment:

Subsequent observation for pneumonia and pulmonary edema. Monitor the circulation.

Monitor the circula

5. Fire-Fighting Measures

5. 1. Extinguishing Media

Suitable extinguishing media:

Foam, carbon dioxide (CO2), extinguishing powder, water spray

iet.

Unsuitable extinguishing media:

Water with full jet.

5. 2. Special Hazards arising from the Substance or Mixture

Special hazards:

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 4

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

Combustible.

Fumes can form an explosive mixture with air.

The vapor is heavier than air, spreads along the ground and

distant ignition is possible.

Product floats on water surface and does not dissolve.

In case of fire: formation of carbon oxides.

5. 3. Advice for Firefighters

Protective equipment:

Wear self-contained respiratory protective device and full

protective gear.

Further information:

Cool exposed containers with water mist.

Collect contaminated extinguishing water and debris separately;

avoid contamination of sewage system.

6. Accidential Release Measures

6. 1. Personal Precautions, Protective Equipment and Emergency Procedures

Personal precautions:

Wear appropriate protective equipment. Keep spectators away.

Close leaks without taking any risk.

Provide adequate ventilation. Keep away from sources of ignition.

6. 2. Environmental Precautions

Environmental precautions:

Prevent contamination of soils, drains and surface water.

Contact local authorities if product pollutes soil or vegetation.

6. 3. Methods and Material for Containment and Cleaning Up

Methods and material:

Contain with absorbent material (sand, diatomaceous earth, acid

binder, universal absorbent) and dispose accordingly.

Dispopse of contaminated material as waste according to section

13.

6. 4. Reference to other Sections

Protective clothing, see Section 8.

7. Handling and Storage

7. 1. Precautions for Safe Handling

Instructions on safe handling:

The usual precautionary measures are to be adhered to when

handling chemicals.

Provide adequate ventilation.

Avoid contact with eyes and skin.

Do not breathe vapors, aerosols.

Hygienic measures:

Take off contaminated clothing immediately.

Keep away from foodstuffs and drinks. Do not eat, drink or smoke during work. Wash hands before breaks and at the end of work.

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 5

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

7. 2. Conditions for Safe Storage, including any Incompatibilities

Storage conditions:

Store in tightly sealed containers in a dry and cool room.

Protect product from direct sunlight.

Product is combustible.

Keep away from ignitable sources and fire.

Requirements for storage areas and

containers:

Store in a room with a solvent-proof floor.

Information on fire and explosion

protection:

Do not store together with: strong oxidants.

Keep away from sources of ignition - do not smoke. Take

measures to prevent electrostatic discharge.

Storage class:

3; Flammable liquids (TRGS 510)

Further Information:

The product is slightly hazardous to water. Consider national

regulations regarding handling and storage.

Storage temperature: 5 - 40°C

7. 3. Specific End Use(s)

Further information:

8. Exposure Controls/Personal Protection

8. 1. Parameters to be Controlled

Parameters to be controlled (DE):

TRGS 900

Hydrocarbons, C9, aromatics:

TLV: 50 mg/m3 (long-term value); 100 mg/m3 (short-term value)

(inhalable dust)

Parameters to be controlled:

Derived No-Effect Level (DNEL):

Hydrocarbons, C9, aromatics:

25 mg/kg bw/d (worker, skin contact, long-term exposure -

systemic effects)

150 mg/m3 (worker, inhalation, long-term exposure - systemic

effects)

11 mg/kg bw/d (consumer, skin contact, long-term exposure -

systemic effects)

32 mg/kg (consumer, inhalation, long-term exposure - systemic

effects)

Predicted No-Effect Concentration

(PNEC):

No values available.

Additional Information:

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 6

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

8. 2. Exposure Controls

Technical protective measures:

No further measures, see Section 7 and 8.

Personal Protection

General protective measures:

Keep away from foodstuffs and drinks. Do not eat, drink or smoke during work. Wash hands before breaks and at the end of work.

Avoid contact with eyes and skin.

Respiratory protection:

Respirator mask required if ventilation is insufficient. Wear filter respirator in case of short-term or low exposure, and wear a self-contained breathing apparatus in case of long-term or higher

exposure.

Recommended: composite filter A-P2 (EN 141)

Hand protection:

Protective gloves. The glove material has to be impermeable and

resistant to the product / substance / preparation.

Protective glove material:

Nitrile rubber (480 min, 0.4 mm)

For short-term exposure: fluoro carbon rubber (FKM)

Eye protection:

Tightly fitting safety goggles (EN 166).

Body protection:

Protective clothing (flame-proof, antistatic).

Environmental precautions:

Avoid contamination of sewage system, open water ways and

ground water.

9. Physical and Chemical Properties

9. 1. Information on Basic Physical and Chemical Properties

Form: liquid

Color: colorless
Odor: pungent

Odor threshold:

no information available

pH-Value:

not applicable

Melting temperature: < -100°C (1 atm)

Boiling temperature: 165 - 180°C (1 atm)

Flash point: > 51°C (1 atm)

Evaporation rate:

No information available.

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 7

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

Flammability (solid, gas):

not applicable

Upper explosion limit: 7.6 Vol.-%

Lower explosion limit: 1.4 Vol.-%

Vapor pressure: 0.2 kPa (20°C)

Vapor density:

No information available.

Density: 0.867 - 0.89 g/cm3 (15°C)

Solubility in water: insoluble

Coefficient of variation (n-

Octanol/Water):

3.7 - 4.5 lowKOW

not applicable

Auto-ignition temperature: > 400°C (1 atm)

Decomposition temperature:

No data available.

Viscosity, dynamic:

not available

Explosive properties:

Product is not explosive; however, an explosive vapor/air mixture

can be formed.

Oxidizing properties:

no information available

Bulk density:

not determined

9. 2. Further Information

Solubility in solvents:

Viscosity, kinematic: < 1 mm2/s (37.8°C)

Burning class:

Solvent content:

Solid content:

Particle size:

Other information:

Surface tension: 29.1 mN/m (25°C)

Temperature class: T2 (maximum temperature: 300°C)

10. Stability and Reactivity

10.1. Reactivity

No decomposition if used according to specifications.

10.2. Chemical Stability

Stable if used according to specifications.

According to regulation (EC) No. 1907/2006 (REACH)

KREMER

70520 Shellsol® A

Page 8

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

10.3. Possibility of Hazardous Reactions

Formation of explosive vapor-air-mixtures possible.

10.4. Conditions to Avoid

Conditions to avoid:

Avoid contact with heat, sparks and open fire.

Avoid direct sunlight.

Thermal decomposition:

No further information available.

10.5. Imcompatible Materials

Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Carbon oxides

10.7. Further Information

11. Toxicological Information

11. 1. Information on Hazard Classes as defined in Regulation (EC) No. 1272/2008

Not classified as acute toxic.

Acute Toxicity

Hydrocarbons, C9, Aromatics

LD50, oral: > 5000 mg/kg (rat)

LD50, dermal: > 3160 mg/kg (rabbit)

LC50, inhalation:

No information available.

Primary effects

Irritant effect on skin:

Causes mild skin irritation. Prolonged contact may cause

dermatitis.

Irritant effect on eyes:

Causes eye ailments, however does not damage the eye tissue.

Inhalation:

Irritates the respiratory tract.

Ingestion:

No information available

Sensitization:

No sensitizing effects known.

Mutagenicity:

No mutagenic effects observed.

Reproductive toxicity:

No relevant data found.

Carcinogenicity:

No negative effects.

Teratogenicity:

According to regulation (EC) No. 1907/2006 (REACH)

Shellsol® A 70520



D	_
Page	Ų
i ugo	

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022 No information available. Specific target organ toxicity (STOT): Single exposure: may cause respiratory irritation. Single exposure: may cause drowsiness or dizziness. Repeated exposure: the substance or mixture is not classified as specific target organ toxicant. Aspiration hazard May be fatal if swallowed and enters airways. 11. 2. Information on other Hazards Skin contact: repeated exposure may cause skin dryness or cracking. 12. **Ecological Information** 12. 1. **Aquatic Toxicity** Hydrocarbons, C9, Aromatics Fish toxicity: LL50: 9.22 mg/l (96h, Oncorhynchus mykiss) Daphnia toxicity: EL50: 3.2 mg/l (48h, Daphnia magna; OECD 202) Bacteria toxicity: EC50: > 99 mg/l (10 min, Microorganisms) Algae toxicity: EC50: 0.29 mg/l; ErC50: 0.42 mg/l (72h, Algae) 12. 2. **Persistency and Degradability** 54 - 56 %, CO2-formation Readily biodegradable. 12.3. Bioaccumulation log KOW: 3.7 - 4.5 (Bioaccumulative) Bioconcentration factor (BCF): 39.8 - 177.8 12.4. Mobility Weak mobility. Product floats on water and is not soluble in water. Adsorption: Adsorption coefficient (Organic Carbon): 2.68 - 3.32 12. 5. Results of PBT- und vPvP Assessment This product is neither a PBT or vPvB substance nor does it contain a PBT or vPvB substance. 12. 6. **Endocrine Disrupting Properties** Not listed. 12.7. Other Adverse Effects

sewage system.

Behaviour in sewage systems:

Further ecological effects:

Water hazard class:

2 (German Regulation) (Assessment by list): hazardous. Do not let product contaminate ground water, waterways or

According to regulation (EC) No. 1907/2006 (REACH)



70520 Shellsol® A

Page 10

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

Toxic to water organisms.

May cause long-term adverse effects in the aquatic environment.

AOX Value:

13. Disposal Considerations

13. 1. Waste Treatment Methods

Product:

Must not be disposed together with household garbage.

Do not let product enter water systems.

Product can be incinerated, when in compliance with local

regulations.

European Waste Code (EWC):

Uncleaned packaging:

Dispose of according to official local regulations.

Non contaminated packaging can either be recycled or utilized for

energy (incineration).

Do not puncture, cut or weld uncleaned drums. Risk of explosion.

Waste Code No.:

14. Transport Information

14. 1. UN Number

ADR, IMDG, IATA 1268

14. 2. UN Proper Shipping Name

ADR/RID: ERDÖLDESTILLATE, FLÜSSIG, N.A.G. (Kohlenwasserstoffe, C9),

SV 664

IMDG/IATA: PETROLEUM DISTILLATES, LIQUID, N.O.S. (Hydrocarbons, C9),

SP 664

3

14. 3. Transport Hazard Classes

ADR Class:

Hazard no.: 3

Classification code: F1

Tunnel restriction code: D/E

IMDG Class (sea): 3

Hazard no.: 3

EmS No.: F-E, S-E

IATA Class: 3

Hazard no.: 3

14. 4. Packaging Group

ADR/RID: III

IMDG:

IATA:

According to regulation (EC) No. 1907/2006 (REACH)

70520 Shellsol® A



Page 11

Revised edition: 02.03.2021 Version: 9 Printed: 19.10.2022

14. 5. Environmental Hazards

Labelling according 5.2.1.8 ADR/RID: fish and tree Labelling according 5.2.1.6.3 IMDG: fish and tree

Classification as environmentally hazardous according 2.9.3

IMDG: yes

14. 6. Special Precautions for User

not applicable

14. 7. Maritime Transport in Bulk according to IMO Instruments

IMDG: not applicable

14. 8. Further Information

Special Provision: 664

15. Regulatory Information

15. 1. Safety, Health and Environmental Regulations/Legislation specific for the Substance or Mixture

Water hazard class:

2, hazardous for water (German Regulation)

Local regulations on chemical accidents:

Underlies the Accident Ordinance 13

Employment restrictions:

The employment restrictions for young workers in accordance with

the Youth Employment Protection Law are to be observed.

The employment restrictions for expectant and nursing mothers in accordance with the Maternity Protection Guideline are to be

observed.

Restriction and prohibition of application:

Technical instructions on air quality:

15. 2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this

product.

15. 3. Further Information

VOC Content: 100 %

16. Other Information

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations. This information contained herein is based on the present state of knowledge and is intended to describe our product from the point of view of safety requirements. It should be therefore not be construed as guaranteeing specific properties.